



NOTES:

- ALL DIMENSIONS ARE IN MMS, WITH INCH IN PARENTHESIS.
- Recommended PC-Board-holes diameter: $\phi 1.20\text{mm}$ to 1.40mm ($\phi 0.047''$ to $\phi 0.055''$)
- THE PART NO. DETAIL SEE DWG NO.=025-0000-017.
- ROHS Directive compliance. (Lead-Free)Wave solder capable to 265°C , $10 \pm 0.5\text{sec}$.

N=Number of contacts

PITCH	3.50mm (.138")	7.00mm (.275")
MODEL:	*-302-***1-***...	*-302-***2-***...
DWG:		

DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH		NAME: (302) NEXTRON 3.5MM TERMINAL BLOCKS	
GENERAL TOLERANCES: (UNLESS SPECIFIED)		PART NO: SEE TABLE	
	mm	INCH	TITLE: ASSEMBLY DWG. ^c
4 PLACE	$\pm .15$	$\pm .006$	APPD:
3 PLACE	$\pm .20$	$\pm .008$	CHKD:
2 PLACE	± 0.20	$\pm .008$	DWG. NO: 010-0000-061
1 PLACE	± 0.15	$\pm .006$	SCALE: 4 / 1
ANGULAR:	$X^{\circ} \pm .5$	$X^{\circ} \pm .02$	SHEET: 1 / 1
REV.	ECN. NO.	DESCRIPTION	DATE
1			6/1.06

REV.	ECN. NO.	DESCRIPTION	DATE	DRAWN	APPD
1			6/1.06		